



## Toro GreenKeeper® 212 Controller 2, 4, 6, 8, 10 or 12 Stations

The GreenKeeper 212 controller is worth another look. With a new look and added features, it's even more of a value. And it's still the most advanced and flexible controller in the industry for residential applications.

### Features

- 2 to 12 stations, expandable with 2-station modules (base model offered with 4 stations)
- Advanced, solid-state design with easy-to-use hybrid interface
- 3 fully independent irrigation programs; any station can be assigned to any program
- Station run times from 1 minute to 4 hours in 1-minute increments
- Independent Season Adjust setting by program from 10-200% in 10% increments
- Automatic split-cycle mode when Season Adjust is greater than 100%, prevents runoff
- Professional, UV-resistant, dark-gray coloring
- 7-day calendar or interval watering cycle; independent by program
- 365-day calendar with true odd- or even-day watering schedule
- Large, clear display and icons for easy programming and operation
- Convenient remote capability available for easy installation and servicing
- Toro SurgePro™ System safeguards against lightning and power surges
- Rain delay setting from 1-7 days prevents water waste
- Built-in sensor port with manual override simplifies Rain Switch installation
- Selectable 15-second station delay
- 9-volt alkaline battery (included) backup for time and program memory:
  - 72 hours with Alkaline (included)
  - 24 hours with Ni-MH
- Low-battery indicator
- Built-in trickle charger for Ni-MH battery use
- Battery operation allows Armchair Programming™ prior to installation
- Spare fuse (0.75 amps) included
- Clear Memory feature resets defaults or clears values by program for simple operation
- Master Off function for extended shutdowns
- Integrated Pump Start/Master Valve output
- Screwless wire terminals for easy installation
- Custom wall mounting plate with 3/4" (20mm) conduit inlet
- Optional, UV- and weather-resistant, lockable outdoor cabinet available
- 3-year warranty on controller and remote control

### Electrical Specifications

- Input power:
  - 117 V a.c., 60 Hz (plug-in transformer)
  - 0.20 amps (24 W) maximum
  - UL/CSA-listed transformer
- Station output power:
  - 24 V a.c.
  - 0.35 amps (8 VA) per station maximum
  - 0.35 amps (8 VA) pump/master valve
  - 0.70 amps (17 VA) total load
  - UL listed, CSA certified

### Mechanical Specifications Controller

- Dimensions:
  - 8" W x 8" H x 2 1/4" D (203mm W x 194mm H x 57mm D)
- Valve output:
  - 3/4" (20mm) conduit access (part of mounting plate)

### Outdoor Cabinet


- Dimensions:
  - 9 7/8" W x 13 1/4" H x 5" D (251mm W x 337mm H x 127mm D)

*Note: Specifications subject to change without notice.*

*For more information, contact your local Toro distributor.*



## Toro Rain Switch®



A simple, yet powerful, conservation tool, the Toro Rain Switch prevents countless gallons of water waste by automatically shutting down the irrigation system when it rains.

*The Rain Switch and the GreenKeeper 212 controller are sold separately.*

## Toro EZ-Remote™



Convenient remote capability available for easy installation and servicing.

*The remote and the GreenKeeper 212 controller are sold separately.*

## Specifying Information

Model Number	Description
GK212-04	4-Station Controller
MOD212-02	2-Station Expansion Module
EZR-T	EZ-Remote Transmitter Only
EZR-R	EZ-Remote Receiver Only
EZR-CA03	EZ-Remote 40" Cable Harness Kit*
EZR-CA25	EZ-Remote 25' Cable Harness Kit*
EZR-Kit	EZ-Remote Complete Kit**
GK212-CAB-01	Outdoor Cabinet

For Example:  
When specifying a 6-station GreenKeeper 212 Controller, you would specify:

**GK212-04** and **MOD212-02**

\* Includes modular cable, receiver plug assembly and mounting bracket.  
\*\* Includes receiver, transmitter and 40" harness kit.



The Toro Company • Irrigation Division • An ISO 9001-Certified Facility  
• PO Box 489 • Riverside, CA • 92502 • (800) 664-4740 • www.toro.com

